

# HD CCTV Redefined for your safety

## 720p HDTV Hybrid All-In-One Security Kits



# SDH-P5080

16 Channel HDTV Hybrid DVR security system

### DVR

- SD (12CH) & HD (4CH) hybrid DVR
- 1080p & 720p recording
- 960H (WD1) recording support
- Auto port forwarding with quick connect technology
- HDMI outputs for convenient connection to HDTVs or monitors

### Camera

- 720p HD resolution camera (x 4)
- 600TV lines SD camera (x 4)
- True Day & Night with ICR for perfect color reproduction
- IP66 weather resistant
- Samsung Super Dynamic Range feature to increase the brightness of the dark area (SSDR)
- Night vision up to 82ft



### SSDR (Samsung Super Dynamic Range)

Useful in high contrast or backlight scene. Automatically lightens the dark areas within a scene whilst maintaining the brighter areas at the same level. This ensures that the dark areas become more viewable allowing the operator to view objects in the shadows.




SSDR Off




SSDR On

### SSNRIII (Samsung Super Noise ReductionIII)

The 3<sup>rd</sup> generation of SSNR can be used in low light condition to enhance the image quality. This technology eliminates image noise in low light conditions without creating image blur or ghosting.



SSNRIII Off




SSNRIII On

## SDH-P5080



## Dimensions

Unit : mm (inch)



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

## Specifications

SDR-5200		
<b>DISPLAY</b>		
Video	Inputs	4CH UTP, 12CH BNC (Composite)
	Resolution	1920 x 1080 (Full HD)
	Frame Rate	120fps@1920 x 1080 + 360fps@704 x 480
	Resolution	1920 x 1080 (Full HD), 704 x 480 (SD)
<b>PERFORMANCE</b>		
Operating System	Embedded	Linux
	Compression	H.264
	Record Rate	Up to 120fps@1920 x 1080 + 360fps@704 x 480
	Mode	Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 30fps)
Recording	Event	Video Loss, Motion (Level 1 ~ 10), Alarm, Tampering
	Overwrite Modes	Continuous
	Pre-alarm	Off / 5sec
	Post-alarm	Up to 6hour (5,10, 20, 30sec, 1, 3, 5, 10, 20min, 1, 2, 3, 4, 5, 6hour)
Search & Playback	Search Mode	Date/time, Event, Back up, Motion (*All search included preview function)
	Playback Function	Fast forward / backward (2x, 4x, 8x, 16x, 32x, 64x) *Backward play with I-frame only
		Slow forward / backward (1/2x, 1/4x, 1/8x)
		Step forward / backward *Backward play with I-frame only
Network	Transmission Speed	4CIF 120fps / 2CIF 240fps / CIF 480fps
	Bandwidth	Up to 32Mbps
	Bandwidth Control	Selectable
	Stream	H.264 (4CIF / 2CIF / CIF selectable)
Smart Phone	Max. Remote Users	Search 3 / Live unicast 10 / Live multicast 20
	Protocol Support	TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, RTSP, UPnP
	Monitoring	SmartViewer, Webviewer, Mobile Viewer
	Smart Phone	Android, iOS (iPhone, iPad)
Storage	Protocol Support	RTP, RTSP, HTTP, CGI
	Transmission Speed	CIF Max. 16fps (Single channel) / CIF Max. 4fps (Quad channel)
	Max. Remote Users	Live 1
	Internal HDD	1TB SATA HDD
Security	External HDD / DVD Writer	External HDD (Up to 2TB)
	USB (Back up)	2 USB ports
	File Format (Back up)	BU (DVR player), SEC (Include player)
	Password Protection	1 Admin, 10 Group, 10 User per 1group
<b>INTERFACE</b>		
Monitors	VGA	1 VGA (1024 x 768, 1280 x 1024)
	HDMI	1 HDMI (720p/1080p resolution)
Audio	Inputs / Output	4 line in / 1 line out
	Compression	G.711
Alarm	Sampling Rate	8KHz
	Remote Notification	Notification via e-mail
Connections	Ethernet	1 RJ-45 10/100Mbps Base-T
	USB	USB 2.0, 2 ports (Front)
	e-SATA	e-SATA 3.0
	Application Support	Mouse, Remote control
<b>GENERAL</b>		
Electrical	Input Voltage / Current	12V DC adaptor, 4A, 100 ~ 250V AC, 50/60Hz, 48watt
	Power Consumption	Max. 40W (With 1x HDD)
Environmental	Operating Temperature / Humidity	0°C ~ +40°C (+32°F ~ +104°F) / 20% ~ 85%RH
	Dimensions (WxHxD)	413.0 x 58.6 x 174.0mm (16.26" x 2.31" x 6.85")
Mechanical	Weight (With hard disks)	1.44kg (3.2 lb)
	Language	English, Spanish, French, German, Italian, Polish, Portuguese, Russian, Turkish, Japanese, Czech, Swedish, Danish, Korean, Chinese, Netherland, Thai, Romanian, Serbian, Croatian, Hungarian, Greek

SDC-8340BUN		SDC-5340BCN
<b>ELECTRICAL</b>		
Input Voltage	12V DC (by PoE)	12V DC
	3W	3W
<b>VIDEO</b>		
Imaging Device	1/4" CMOS	1/3" CMOS
	1024 x 720 (720p)	720 x 480
Scanning System	Progressive	Interlace
	Internal	Internal
Frequency	H : 15,734Hz / V : 59.94Hz	H : 15,734Hz / V : 59.94Hz
	800TV lines	600TV lines
Horizontal Resolution	0Lux (IR LED)	0Lux (IR LED)
	50dB	46dB
S/N Ratio (Y Signal)	Built-in UTP TX	N/A
	Maximum transmission length : 150m (UTP CAT 5e)	N/A
UTP Output	Balanced differential impedance : 100 ohm	N/A
<b>LENS</b>		
Focal Length	3.6mm	3.6mm
	2	2
Max. Aperture Ratio	D : 86°	D : 72°
<b>OPERATIONAL</b>		
Shutter Mode	Auto (Rolling shutter)	Auto (Rolling shutter)
	Auto	Auto
Gain Control	Auto (3,200°K ~ 6,500°K)	Auto (3,200°K ~ 6,500°K)
	SSDR (On)	N/A
White Balance	SSNR (On)	Auto
	Auto	Auto
Contrast Enhancement	Auto	Auto
	25m (82ft)	25m (82ft)
<b>ENVIRONMENTAL</b>		
Operating Temperature / Humidity	-10°C ~ +50°C (+14°F ~ +122°F) / 20% ~ 85%RH	-10°C ~ +50°C (+14°F ~ +122°F) / 20% ~ 85%RH
<b>MECHANICAL</b>		
Ingress Protection	IP66	IP66
	70.5 x 70.2 x 200mm (2.78" x 2.76" x 7.87")	70.7 x 61.0 x 192.1mm (2.78" x 2.40" x 7.56")
Dimensions (WxHxD)	240g (0.53 lb)	241g (0.53 lb)

Design and specifications are subject to change without notice.

DISTRIBUTED BY

**SAMSUNG TECHWIN CO., LTD.** 701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400  
Tel : +82-70-7147-8741~8749, 8752~8760 Fax : +82-31-8018-3745 www.samsungsecurity.com www.samsungcctv.com

**SAMSUNG TECHWIN AMERICA INC.**  
100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660  
Customer support : +1-877-349-3149  
www.samsungsv.com

**SAMSUNG TECHWIN EUROPE LTD.**  
2st floor No5, The Height, Brookland, Weybridge, Surrey, U.K.  
KT13 0NY  
Customer support : 00800-8010-8011  
www.samsungsechome.eu

**SHANGHAI SAMSUNG TECHWIN CO., LTD.**  
32F, Bldg B, International Business Center,  
No. 391 Guiping Rd., Shanghai, China, 200233  
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122



SAMSUNG TECHWIN